





PUMP SPECIFICATION

043M - STD - FLOT



43 m3 / Day / 100 RPM (270 bbl / Day / 100 RPM)							
Available Models		043 M 0600	043 M 0900	43 M 1200	043 M 1500	043 M 1800	043 M 2100
ROTOR	Geometry: Single Lobe Operating Speed: 50 - 500 RPM Free Gas Volume Fraction: 40% continuous						
	Swept Rotor Angle: 53	Orbit Helix - mm (in): 66.00 (2.598)		Intake cavity area - mm ² (in ²): 1064 (1.65)			
	Pump Lift H2O - m (ft)	600 (1968)	900 (2952)	1200 (3936)	1500 (4920)	1800 (5904)	2100 (6888)
	Rated Pressure kPa (psi)	6000 (870)	9000 (1305)	12000 (1740)	15000 (2175)	18000 (2611)	21000 (3046)
	Rated Torque N-m (ft-lbs)	328 (241)	492 (362)	656 (483)	820 (604)	983 (724)	1147 (845)
	Rotor Top Connection mm (in)	1" API Pin					
STATOR - STD	Rotor Head Diameter mm (in)	50.80 (2.00)					
	Overall Rotor Length m (in)	3.52 (139)	5.01 (197)	6.49 (256)	8.02 (316)	9.51 (374)	10.99 (372)
	Weight kg (lbs)	30 (66)	45 (99)	60 (132)	75 (165)	90 (198)	105 (231)
	Nominal Rotor Drift OD mm (in)	53.01 (2.087)					
	Stator OD mm (in)	95.0 (3.74)					
	Collar OD (mm)	114.3 (4.50)					
STATOR - FLOT	Connection Discharge - Intake	3 1/2" EUE Pin - 3 1/2" EUE Pin					
	Stator Overall Length w TB m (in)	3.47 (137)	4.96 (195)	6.44 (254)	7.97 (314)	9.46 (372)	10.94 (431)
	Weight kg (lbs)	59 (130)	88 (194)	117 (257)	147 (323)	176 (387)	205 (451)
	Distance TB to Elastomer mm (in)	300 (12)					
	Tagbar/sub bottom connection	3 1/2" EUE Pin					
	Stator OD mm (in)	FLOT - 95 (3.74)					
NOTE	Collar OD mm (in)	FLOT - 98 (3.85)					
	Connection Discharge - Intake	2 7/8" EUE Box - 3 1/2" NUE Box					
	Stator Overall Length w TB m (in)	5.31 (185)	6.79 (243)	8.27 (302)	9.81 (362)	11.29 (420)	12.77 (479)
	Weight kg (lbs)	84 (185)	113 (249)	142 (312)	172 (378)	201 (442)	230 (506)
	Distance TB to Elastomer mm (in)	300 (12)					
	Tagbar/sub bottom connection	2 7/8" EUE Pin					
	Notes: Dimensions for FLOT reflect a 1220 mm (48in) orbit tube. Add 610 mm (24 in) and 12 kg (26 lbs) for extended orbit tubes.						

Target in Well Flow Rates m³/d (bbl/d)



Target In Well Torque N-m (ft-lbs)

